Appl. No. 10/506,487 Amdt. Dated September 26, 2006 Reply to Office Action of June 26, 2006

Amendment to the Claims:

This listing will replace all prior versions, and listings, of the claims in the application:

Listing of Claims:

Claim 1 (Currently amended): A metal- or resin-laminated gasket, which comprises a cured product layer of a composition comprising:

(A) an acrylic polymer having at least one alkenyl group capable of undergoing hydrosilylation reaction obtained by copolymerization of an acrylic acid ester monomer and a compound as a second monomer represented by the general formula:

$$CH_2=CR^1-R^4-CR^1=CH_2$$

wherein R¹ is a hydrogen atom or a methyl group and R⁴ is an <u>alkyl</u> organic group of C₁-C₂₀, which may have at least one ether bond;

- (B) a hydrosilyl group-containing compound; and
- (C) a hydrosilylation catalyst as essential components, and a metal plate or resin plate, the cured product layer being provided on at least one surface of the metal plate or the resin plate.

Claim 2 (Previously presented): A metal- or resin-laminated gasket according to claim 1, wherein the component (A) of the composition is a liquid acrylic polymer having a number

P.06/15

Appl. No. 10/506,487 Amdt. Dated September 26, 2006

1.8 or less.

Reply to Office Action of June 26, 2006

average molecular weight Mn of 500 or more and a molecular weight distribution (Mw/Mn) of

Claim 3 (Previously presented): A metal- or resin-laminated gasket according to claim 1,

wherein the cured product layer has a film thickness of 1-500 μm.

Claim 4 (Previously presented): A metal- or resin-laminated according to claim 1, wherein the

cured product layer has a surface hardness (Duro hardness A) of 45 or less.

Claim 5 (Previously presented): A metal- or resin-laminated gasket according to claim 1,

wherein the composition is directly applied to an adhesive-coated metal plate or resin plate and

cured.

Claim 6 (Previously presented): A metal- or resin-laminated gasket according to claim 1, which

comprises at least one of an automobile engine cylinder head gasket, an engine oil pan gasket and

an engine intake-exhaust manifold gasket.

Claim 7 (Previously presented): A metal- or resin-laminated gasket according to claim 1,

wherein the cured product is provided on a resin plate that has a softening point of 100°C or

more.

٠4

SEP 26 '06 10:30 FR BUTZEL LONG/ANN ARBOR734 668 0770 TO 15712738300 P.07/15

Appl. No. 10/506,487

Amdt. Dated September 26, 2006

Reply to Office Action of June 26, 2006

Claim 8 (Previously presented): A metal- or resin-laminated gasket according to claim 2, which

comprises at least one of an automobile engine cylinder head gasket, an engine oil pan gasket and

an engine intake-exhaust manifold gasket.

Claim 9 (Previously presented): A metal- or resin-laminated gasket according to claim 3, which

comprises at least one of an automobile engine cylinder head gasket, an engine oil pan gasket and

an engine intake-exhaust manifold gasket.

Claim 10 (Previously presented): A metal- or resin-laminated gasket according to claim 4, which

comprises at least one of an automobile engine cylinder head gasket, an engine oil pan gasket and

an engine intake-exhaust manifold gasket.

Claim 11 (Previously presented): A metal- or resin-laminated gasket according to claim 2,

wherein the cured product is provided on a resin plate that has a softening point of 100°C or

more.

Claim 12 (Previously presented): A metal- or resin-laminated gasket according to claim 3,

wherein the cured product is provided on a resin plate that has a softening point of 100°C or

morc.

5

PAGE 7/15* RCVD AT 9/26/2006 12:28:13 PM [Eastern Daylight Time] * SVR:USPTO-EFXRF-6/36 * DNIS:2738300 * CSID:734 668 0770 * DURATION (mm-ss):04-00

P.08/15

Appl. No. 10/506,487 Amdt. Dated September 26, 2006 Reply to Office Action of June 26, 2006

Claim 13 (Previously presented): A metal- or resin-laminated gasket according to claim 4, wherein the cured product is provided on a resin plate that has a softening point of 100°C or more.

Claim 14 (Previously presented): A metal- or resin-laminated gasket according to claim 1, wherein the second monomer is one of 1,5-hexadiene, 1,7-octadiene and 1,9-decadiene.

Claim 15 (Currently amended): A metal- or resin-laminated gasket according to claim 1, wherein the second monomer reacts at a final stage of the polymerization react reaction or after completion of the reaction of the acrylic acid ester monomer in the synthesis of acrylic polymers by living radical polymerization.